

# LPU-2428 Loop Powered Ultrasonic Level Sensor



Flexible by Design

With Class 1 Division 1 ratings, the loop powered LPU-2428 is built to handle the most hazardous locations. Add the ability to internally calculate volume or open channel flow data, and you have a unique and powerful ultrasonic sensor.

## Features

- Loop powered 4-20 mA output
- Class 1 Division 1 rating
- Built-in calculations of current volume, flow, and flow totals

**W. H. Cooke & Co., Inc.**

[sales@whcooke.com](mailto:sales@whcooke.com)

Manufacturer of thermocouples & RTD's Made in the USA  
Supplier of industrial controls, heaters, and sensors since 1963

717-630-2222

# LPU-2428 Specifications



## Performance

- Operating Range
  - 1 - 25 ft. (0.3 - 7.6 m) on liquids
  - 1 - 10 ft. (0.3 - 3 m) on solids
- Beam Pattern: 9° off axis
- Internal Temperature Compensation
- Frequency: 69 kHz
- Accuracy:  $\pm 0.25\%$  of detected range
- Resolution: 0.1 in. (2.5 mm)
- Response Time: Output dependent on output ranges from 0.6 - 3 seconds

## Connectivity

- Output:
  - 4-20 mA (loop powered)
  - 600 ohms @ 24 VDC
  - 150 ohms @ 12 VDC
- Network/Web with the RST-5001

## Environmental

- Ratings: IP65
- Operating Temp: -40° - 140°F (-40° - 60°C)

## Certification

- Class 1, Div. 1, Groups C & D
- Class 1, Zone 0, AEx iA IIB, T3; IP65

## Electrical

- Total Current Draw: 4-20 mA
- Supply Voltage: 12-28 VDC
- Wiring Connection: 2-conductor shielded cable

## Programming

- Interface with RST-4001 Programmer (purchase separately)
  - The RST-4001 is powered by an internal 9v battery or a USB port connecting the RST to a computer. A 2-conductor terminal strip allows the programmer to be connected in parallel with the 4-20 mA loop.
- Volume Measurement Settings:
  - Formulas for a wide variety of common tank types
- Flow Measurement Settings:
  - Formulas for a wide variety of weirs and flumes
  - total flow counter
- 32-point linearization table for unique tanks, weirs, and flumes
- User selected units of measure

## Physical

- PVDF (Kynar®) transducer housing
- PC/PBT upper housing
- Transducer Type: Ceramic, PVDF faced

## Options

LPU-2428 - \_\_\_\_\_ Cable length in feet (6 ft. is standard)