



Trident Now With
2 RELAYS +
4-20 mA OUTPUT
Together in One Meter



PRECISION DIGITAL 



Actual Size Digit



PD765 Trident X2



PD8-765 ProtEX-MAX




- Now available with **2 Relays + 4-20 mA Output** together in one meter.
- 85-265 VAC powered models include a **24 VDC Transmitter Power Supply**.



POWERFUL

2 Relays + 4-20 mA Output Together in One Meter




The Trident, Trident X2, and PD8-765 are now available with **2 Relays + 4-20 mA Output** together in one meter. The 85-265 VAC powered models also include a **24 VDC Transmitter Power Supply**.

- Use the 2 relays for local dual pump alternation level control and use the 4-20 mA output to retransmit to a plant-wide control system.
 - Use the 4-20 mA output and Trident X2 for local indication of transmitters and use the 2 relays as high and low alarms.
-

VERSATILE

Field Selectable Process & Temperature Inputs

- ± 20 mADC (0-20, 4-20 mA)
- ± 10 VDC (0-5, 1-5, 0-10 V)
- J, K, T, E thermocouples
- 100 Ω platinum RTD



AMAZING

Trident Exceeds Expectations



- Trident X2, the largest 1/8 DIN process & temperature display on the market, 1.2" (30.5 mm) high
 - Competitively priced full-featured models
 - Fast delivery and outstanding support
 - Ideal for level, flow, temperature, or pressure applications
-