

REOTEMP SILICONE-FILLED THERMOMETERS

PRODUCT INFORMATION

FLUID: SILICONE (POLYDIMETHYLSILOXANE)

CRYSTAL: PLASTIC (POLYCARBONATE)

OPERATING CONDITIONS: THE TEMPERATURE OF THE CASE SHOULD NOT EXCEED 150 DEG. F (65 DEG. C). HIGHER TEMPERATURES MAY CAUSE EXCESS PRESSURE WHICH COULD RESULT IN FAILURE OF THE CRYSTAL, AND SEE PAGE OF FLUID FROM THE CASE.

THERMOWELLS: USE OF A THERMOWELL IS REQUIRED FOR ANY APPLICATION WHERE THE STEM IS EXPOSED TO PRESSURE, CORROSIVE FLUIDS, OR SHEAR FORCES.

SFINST.0203

REOTEMP SILICONE-FILLED THERMOMETERS

PRODUCT INFORMATION

FLUID: SILICONE (POLYDIMETHYLSILOXANE)

CRYSTAL: PLASTIC (POLYCARBONATE)

OPERATING CONDITIONS: THE TEMPERATURE OF THE CASE SHOULD NOT EXCEED 150 DEG. F (65 DEG. C). HIGHER TEMPERATURES MAY CAUSE EXCESS PRESSURE WHICH COULD RESULT IN FAILURE OF THE CRYSTAL, AND SEE PAGE OF FLUID FROM THE CASE.

THERMOWELLS: USE OF A THERMOWELL IS REQUIRED FOR ANY APPLICATION WHERE THE STEM IS EXPOSED TO PRESSURE, CORROSIVE FLUIDS, OR SHEAR FORCES.

SFINST.0203

REOTEMP SILICONE-FILLED THERMOMETERS

PRODUCT INFORMATION

FLUID: SILICONE (POLYDIMETHYLSILOXANE)

CRYSTAL: PLASTIC (POLYCARBONATE)

OPERATING CONDITIONS: THE TEMPERATURE OF THE CASE SHOULD NOT EXCEED 150 DEG. F (65 DEG. C). HIGHER TEMPERATURES MAY CAUSE EXCESS PRESSURE WHICH COULD RESULT IN FAILURE OF THE CRYSTAL, AND SEE PAGE OF FLUID FROM THE CASE.

THERMOWELLS: USE OF A THERMOWELL IS REQUIRED FOR ANY APPLICATION WHERE THE STEM IS EXPOSED TO PRESSURE, CORROSIVE FLUIDS, OR SHEAR FORCES.

SFINST.0203