SML Air Pressure Switch



SML

The SML air pressure switch features a sensitive diaphragm to detect changes in air pressure. Easy to install and reliable, this switch is available in two range scales and with an optional neon light indicator.

Features

- Sensitive diaphragm.
- Snap-action electrical switch S.P.D.T. rated at 10 amps.
- Industrial combustion.
- Two range scales from .05" W.C. to a maximum of 9" W.C.
- Easy to install.
- Cost-effective pricing.

Antunes Controls

Since 1962, Antunes Controls has designed and manufactured exceptional quality products for applications that require precision mechanisms. From our earliest pressure switches, which are still manufactured today with only slight modifications, to our more advanced electronic controls and timers, Antunes Controls uses only the highest quality components and the highest standards to ensure each one of our products is durable and dependable. That is why our switches and controls can be found in buildings throughout the world.

For more information about Antunes Controls and its products, call (630) 784-1000 or visit www.antunescontrols.com.



Antunes Controls

Air Pressure Switch

Dimensions

Standard Inlet Locations (1/8" NPT Without Fittings)



1/4" Barb

1/4" Tube

1/4" Compression

Option: Neon Light Indicator



Specifications

Electrical Ratings:

10A @ 125 VAC.; 8A @ 250 VAC.; 7A @ 277 VAC.; 1/8HP @ 125 VAC, 1/4HP @ 250 VAC Pilot Duty, 125VA @ 125/277 VAC

Max. Surge Pressure: 20" W.C.

Max. Ambient Temperature: 170°F (77°C)

Min. Ambient Temperature: -40°F (-40°C)

Shipping Weight: 1 lb. (.45 kg)

Limitation of Liability. If it is understood and agreed that seller's liability whether in contract, in tort, under any warranty, in negligence or otherwise, shall not exceed the return of the amount of the purchase price paid by purchaser and under no circumstances shall seller be liable for special, indirect or consequential damages. The price stated for the equipment is a consideration in limiting seller's liability. No action, regardless of form, arising out of the transactions may be brought by purchaser more than one year after the cause of action has accrued.

P/N 1020377 Rev. A 12/12

Antunes Controls

USA Headquarters: Ph: (630) 784-1000 China Facility: Ph: 86-512-6841-3637 Fx: 400-0-7878-22 Tf: 86-512-6841-3907

Fx: (630) 784-1650 Tf: (800) 253-2991