

InteliHeat® Class I Zone I 15-gallon (50 Liter) Heating Jacket (IHFNA/B/Z1)

Our InteliHeat® CIZ1 15-gallon Heating Jacket certified for use in Class I Zones 1 and 2 Classified Hazardous Locations is ideal for gently warming and to avoid winter freezing. Unique self-limiting design ensures safe operating conditions are maintained even in the presence of gasses and dusts without the need for a thermostat (thermostatic control available if needed).

- Chemically resistant silicone coated glass cloth used on outer surfaces to extend product life in demanding applications.
- High grade thermal insulation to reduce heat loss and increase efficiency while providing protection for the operator.
- Fitted with adjustable retaining straps and quick release buckles.
- Flexible - conforms to the container wall providing optimal thermal coupling
- Delivers heat over a large surface area, minimizing the possibilities of damaging the product.
- Fit and forget, built to last - no regular maintenance required.
- Safe to use 24/7.
- 16 ft. (5m) premium oil, water, and abrasion resistant SOOW power cable
- Double insulated product
- Ambient temperature: -40°F to +104°F (-40°C to +40°C)
- ETL approved to UL and CSA standards. Suitable for Class I Zone 1 Hazardous locations.
- A self-limiting temperature will be maintained on the container wall of around 104°F(40°C) above ambient temperature.
- Waterproof and custom sizes available.

Hazardous Location Marking:

AEx e IIB+H2 T3 Gb, Ex e IIIB+H2 T3 Gb

Class I Zone I, IIC, T3. Class II Division 2 Groups EFG T3

T4 rating available on request

To fit container: 15 Gallon / 50 Liter

Thermostat: N/A

Size: Circumference 43.25" – 49.25" / Height 18" (1100 – 1250mm / 460mm)

240 Volts

130 Watts

Part Number: IHFNA/B/Z1/#/I/240/130