

InteliHeat® Thermulate® Full Coverage 55-gallon Heating Jacket (HPNA/D2/OR)

Our InteliHeat® Thermulate® HPD2 Full Coverage 55-gallon Heating Jacket certified for non-hazardous ordinary locations provides maximum power to reach highest temperatures quickly and efficiently.

- Ideal for melting solids
- Two independently controlled upper and lower heating zones
- 32-320°F (0-160°C) adjustable thermostats fitted as standard to each upper and lower circuit for optimal temperature control
- Special formulated high-temperature, chemically resistant silicon-coated glass-cloth used on both sides of the jacket to extend product life in demanding applications
- High-grade thermal insulation to reduce heat loss and increase efficiency while providing protection for the operator
- Rugged and reliable
- Suitable for both plastic and steel 55 gallon (200 liter) drums
- Flexible and built to last
- Conforms to drum walls and rings providing optimal thermal coupling
- Fitted with adjustable retaining straps and quick release buckles
- Delivers heat over a large surface area, minimizing the possibilities of damaging the product
- Fit and forget - no regular maintenance required
- Safe to use 24/7
- Ambient temperature: -40°F to +104°F (-40°C to +40°C)
- 2600 Watts at 120 VAC
- 240 VAC versions also available
- 7 ft. (2m) premium oil, water, and abrasion resistant SOOW power cable
- -S Usage marking and area of use for weather resistance
- Double insulated product
- ETL approved to UL and CSA standards
- Waterproof and custom sizes available

North American Certifications and Markings:

Listed, ETL Control Number: 5001878

Conforms to ANSI/UL Std. 499, Cert to CAN/CSA Std.C22.2 No.130-03

